



**DESCRIPTION**

The Magma 5 is a multi-function very small loudspeaker for mobile and fixed installation applications, especially where high SPLs needed. Magma 5 can be used as a mini floor monitor. A 5" LF transducer and a 1" conical horn-loaded compression driver produce a maximum output of 118 dB SPL, the unit exceed most performance comparable devices. The extraordinary power handling capability of this Magma system means that it can comfortably and reliably reproduce a range of program setup with very low distortion and power compression.

The pilotage need only one amplifier channel, the frequency splitting being accomplished by the low-loss passive filter passive crossover network inside the enclosure manufactured with top grade components, including coils with very low resistance and metalized polypropylene capacitors. It also features circuitry to protect the HF component against excessive current and voltage. Personalized setup available for Powersoft sytem amplifier. The cabinet is from Baltic birch features craftsmanship protected by an epoxy powder coated, resonance-free steel grill over acoustically transparent foam. Every cabinet is coated with a high-tech black textured polwater scratch free finish and custom RAL is possible on request. The system includes mounting hardware, compatible with various separately available mounting brackets.

**FACILITIES**

Auditorium, concert halls, houses of worship, shopping centers, conference rooms, sport facilities, retail stores industrial, commercial and leisure projects, pubs, bars and cafes, small theatrical installations, schools malls hotels.

**APPLICATIONS**

Mini PA System, Under Balcony, Foreground Music Systems, Background Music Systems, Paging Systems, Delay and Stage front fill, Mini floor monitor system.

**PERFORMANCE**

Frequency Response -10 dB 70 Hz – 22 kHz  
 Nominal Dispersion 80° x 80° (H x V)  
 Impedance (Nom) 8 Ω  
 Watts AES Continuous 120 W/Peak 250 W  
 Maximum SPL Output calculated 118 dB SPL

**PHYSICAL**

Component Low 5" woofer  
 Component High 1" diaphragm compression driver  
 Loading Low Bass-reflex  
 Loading High 1" Conical Horn  
 Connectors 4 x NL4 PAR Pins 1+/1-  
 Cabinet Material Baltic birch plywood  
 Cabinet Finish Black polywater coating  
 Grill Epoxy powder coated  
 Installation Points 8 x M6  
 Pole Mount 35 mm socket  
 Height 330 mm  
 Width 180 mm  
 Depth 200 mm  
 Weight 5.9kg

**DIMENSION 5**

