









DESCRIPTION

The Magma 8 is a multi-function very compact loudspeaker for mobile and fixed installation applications, especially where high SPLs needed. Magma 8 can be used as a mini floor monitor. A 8" LF transducer and a 1.4" HF driver on rotable horn produce a maximum output of 123 dB SPL, the unit exceed most performance comparable devices. The extraordinary power handling capability of this Magma system means that it can comfortably and reliably reproduce a range of program setup with very low distortion and power compression.

The pilotage need only one amplifier channel , the frequency splitting being accomplished by the low-loss passive filter passive crossover network inside the enclosure manufactured with top grade components, including coils with very low resistance and metalized polypropylene capacitors. It also features circuitry to protect the HF component against excessive current and voltage. Personalized setup aviilable for Powersoft sytem amplifier. The cabinet is from Baltic birch features craftsmanship protected by an epoxy powder coated, resonance-free steel grill over acoustically transparent foam. Every cabinet is coated with a high-tech black textured polwater scratch free finish and custom RAL is possible on request. The system includes mounting hardware, compatible with various separately available mounting brackets.

FACILITIES

Auditorium, concert halls, houses of worship, shopping centers, conference rooms, sport facilities, retail stores, industrial, commercial and leisure projects, pubs, bars and cafes, small theatrical installations, schools malls hotels.

APPLICATIONS

Mini PA System, Under Balcony, Foreground Music Systems, Background Music Systems, Paging Systems, Delay and Stage front fill, Mini floor monitor system.

PERFORMANCE

Frequency Response -10 dB 65 Hz - 22 kHz Nominal Dispersion 90° x 40° (H x V) Impedance (Nom) 8 Ω Watts AES Continous 310 W/Peak 875 W Maximum SPL Output calculated 123 dB SPL

PHYSICAL

Component Low 8" woofer
Component High 1.4" diaphragm compression driver
Loading Low Bass-reflex
Loading High 1" Rotable Horn
Connectors 2 x NL4 PAR Pins 1+/1-

Cabinet Material Baltic birch plywood

Cabinet Finish Black polywater coating

Grill Epoxy powder coated Installation Points 8 x M6

Installation Points 8 x Mid

Pole Mount 35 mm socket

Height 500 mm

Width 240 mm

Depth 250 mm

Weight 10.2kg

DIMENSION 8

