

ST17

MICRO VERTICAL LINE ARRAY SYSTEM



- Dual 6" LF Neodymium in Vented Enclosure
- 1,4" Titanium Driver (3" VC) on Wave Guide
- Fly Mounting Hardware Included
- Powering Mode: Full Range Passive or Bi-Amp
(with Internal Passive Crossover)
- For Touring or Permanent Installation

Product Information

2-WAY loudspeaker system provides higher output, lower distortion sound reinforcement for the entire range of pro audio application. The 152 mm (6") low frequency cone with 45 mm (1.75") voice coil with Neodymium magnet and 75 mm (3") voice coil high frequency compression driver provides higher output and low distortion plus enhanced power handling capabilities for better performance in both touring and permanently installed applications. ST17 is designed specifically for vertical curvilinear array.

Data Sheet

Frequency Response	±3 dB 75 Hz ~ 18 KHz -10 dB 58 Hz
Sensitivity (1 Watt @ 1 m)	98 dB
Max SPL Calculated (Power AES) [PEAK]	125 dB [129 dB]
Nominal Input Impedance (Ω)	16 Ω
Power Handling (Watts Cont. AES) [PEAK]	510 W [1220 W]
Nominal Dispersion (@ -6 dB)	120° (H) x 9° (V)
Dimensions mm (±1 mm) (H x W x D)	195 x 580 x 520 with Harware
Weight	14 Kg

Enclosure Material

- Enclosure Material: Birch Plywood of 15 mm
- Finish: Texture Polyurethane Black Paint
- Suspension: 3+3 Point Mounting Suspension
- Grille: Powder Coated Perforated Steel with anti-dust foam
- Connectors: 2 Neutrik NL4 Speakon
- Optional Accessories: Flight Case for 4 ST17, Pole Mounting Adapter

ARRAY SYSTEMS | INSTALL | TOURING

